

DW315

Widescreen, bright, vibrant and Portable

- Bright WXGA projector 3000 ANSI Lumens
- Accurate colours sRGB
- Easy connectivity HDMI, VGA, 2W speaker
- Lightweight and portable



















DW315

Widescreen, bright, vibrant and portable

Project bright vibrant presentations in HD effortlessly any time of day. Designed for meeting rooms and classrooms, the DW315 boasts sRGB accurate true to life colour reproduction, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs and a built-in speaker. Perfect for connecting a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

Amazing Colour

Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs.





Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

Energy saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance

High contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.





Full 3D

Optoma projectors can display true 3D content from almost any 3D

source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.

Integrated speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

Eco AV mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto power off" feature automatically turns off the projector after a set period of time.

Long lamp life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.

Colour Guarantee

We are so confident that the image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Wireless

Stream Full 1080p 3D content to your projector wirelessly; eliminating the hassle and extra cost of installing long cables, the WHD200 (sold separately) allows you to connect a Blu-ray[™] player, set-top box, gaming console or AV receiver instantly.

Quick resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

DW315 Specification

Native Resolution WXGA 1280 x 900 Brightness* (Bright Mode) 3000 ANSI Lumens Contrast 20,000:1 Lamp Life* Eco+/Dynamic/Eco/Bright 8000/7000(6000/5000 (firs) Throw Ratio 1.55 - 1.73:1 Zoo Tonecros 1.1x Manual Support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service Speaker (Watts) 2 Keystone Correction 4 40" Vertical Weight (Kg) 2.17 Dimensions (W x 0 x H) (mm) 2.28 x 230 x 96 S Aspect Ratio 16.10 Native, 15.94:3 Compatible Official 112.4% Projection Screen Size 0.68 - 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Distance 1 - 12m Vindomity 75% Vindomity 75% Vindomity 75% Vido Compatibility 75% Fill 3D - 1 H J, N, WA, 4.33MHz), NTSC (M, J, 3.58MHz, 4.43MHz), SECAM (B, D, G, K, K1, L, 425,MHz, 4.44MHz, 480ly, 576(b), 720(b)(500(b), 2.000(c)00(c)), 2.000(c)00(c)00(b), 2.000(c)00(c)00(b), 2.000(c)00(c)00(c) 3D Support Full 3D - 1 he 3D features of Optiona projectors can only be used with	Display Technology	Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments
Contrast		0, ,
Contrast 20,000:1 Lamp Life ² Eco+/Dynamic/Eco/Bright 8000/7000(8000)(8000) (hrs) Throw Ratio 1.55 - 1.73:1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service Speaker (Watts) 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 112.4% Projection Distance 1 - 12m Projection Distance 1 - 12m Projection Distance 1 - 12m Projection Compatibility 75% Video Compatibility 75% Video Compatibility PAL (B, 0, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3 58MHz, 4.43MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480l/p, 576lip, 720(5)(6)00Hz), 1000(6)00(6)00(1) 2000(2)(2450(6)00Hz), 1000(2)(2450(6)00Hz), 1000(2)(2450(6)00	Brightness ¹ (Bright Mode)	3000 ANSI Lumens
Throw Ratio 1.55 - 1.73.1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPt/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service Speaker (Watts) 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:04/3 Compatible Offset 112.4% Projection Screen Size 0.8a – 8.04m (26.87° to 316.5°) Diagonal 16:10 Projection Distance 1 – 12m Projection Distance 1 – 12m Projection Compatibility 75% Video Compatibility 75% PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480Hz), 576(p, 7.20p.600Hz), 1098(p)60Hz), 1098(p)62(45/608Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems (SKY in the UK), Blur-ay 3D ™ and 3D games from the Sony® PS sor Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 760, 720p50 760 Frame-pack: 1080p24, 720p50		20,000:1
Throw Ratio 1.55 - 1.73.1 Zoom Type 1.1x Manual I/O Connectors HDMI (1.4a 3D support), VGA (YPbPt/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service Speaker (Watts) 2 Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:04/3 Compatible Offset 112.4% Projection Screen Size 0.8a – 8.04m (26.87° to 316.5°) Diagonal 16:10 Projection Distance 1 – 12m Projection Distance 1 – 12m Projection Compatibility 75% Video Compatibility 75% PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480Hz), 576(p, 7.20p.600Hz), 1098(p)60Hz), 1098(p)62(45/608Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems (SKY in the UK), Blur-ay 3D ™ and 3D games from the Sony® PS sor Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 760, 720p50 760 Frame-pack: 1080p24, 720p50	Lamp Life ² Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 (hrs)
200m Type		` '
IDO Connectors		
Speaker (Watts) 2		
Keystone Correction ± 40° Vertical Weight (kg) 2.17 Dimensions (W x D x H) (mm) 298 x 230 x 96.5 Aspect Ratio 16:10 Native, 16:94:3 Compatible Offset 112.4% Projection Screen Size 0.88 = 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Lens F/2.5~2.67; f=21.86~24mm Uniformity 75% Computer Compatibility PHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480l/p, 576l/p, 720p(50/80Hz), 1080l(50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors anonly be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY) in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 24 - 85Hz (120Hz for 3D) Uspiayable Colours 1073.4 Million Noise Level (Eco mode) 294B Power Consumption 225W Bright mode / 187W Eco m		
Veright (kg) 2,17		
Dimensions (W x D x H) (mm) 298 x 230 x 96.5		
Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 112.4% Projection Screen Size 0.68 = 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 - 12m Projection Lens Fi2.5-2.67; =21.86-24mm Uniformity 75% Computer Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080l(50/60Hz), 1080l(50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors on only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Furne-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 15.3 - 91.1kHz Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby)		
Offset 112.4% Projection Screen Size 0.68 – 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 – 12m Projection Lens F/2.5-2.67; f=21.86-24mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz, 443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480ip, 576ip, 720p(50/600Hz), 1080i(50/600Hz), 1080i(50/60Hz), 1080		
Projection Screen Size 0.68 − 8.04m (26.87" to 316.5") Diagonal 16:10 Projection Distance 1 − 12m Projection Lens Fi2.5~2.67; f=21.86~24mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby)	<u> </u>	
Projection Distance 1 − 12m Projection Lens F7.2.5−2.67; f=21.86−24mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.40MHz, 480//p, 576//p, 720p(506)Hz), 1080/(506)Hz), 1080/(506)		
Projection Lens F/2.5~2.67; f=21.86~24mm Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080b(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projector can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Over-Under: 1080p24, 720p5		, ,
Uniformity 75% Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 443MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.40/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount	,	· · · · · · · · · · · · · · · · · · ·
Computer Compatibility FHD, HD, WXGA, UXGA, SXGA, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) Displayort Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Pover-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Pover Supply Power Consumption Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Gerek, Hungarian, Czech, Arabic, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories Optional Mireless Yes		,
PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50)60Hz), 1080p(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 080p24, 720p50 / 60 Power Under: 080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1 kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Mireless Yes		
S76i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display Security bar, Kensington lock, password protection On Screen, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories OLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsots(® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 86Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories Optional Accessories OLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	video Compatibility	
games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	3D Support	
Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		
Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Wireless Yes	3D Compatibility	•
Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabito, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Wireless Yes	ob companionity	
Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1073.4 Million Noise Level (Eco mode) 29dB Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		
Displayable Colours1073.4 MillionNoise Level (Eco mode)29dBPower Supply100-240V, 50-60HzPower Consumption225W Bright mode / 187W Eco mode (< 0.5W Standby)	Horizontal Scan Rate	
Noise Level (Eco mode) Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Displayable Colours	1073.4 Million
Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Noise Level (Eco mode)	29dB
Power Consumption 225W Bright mode / 187W Eco mode (< 0.5W Standby) Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Power Supply	100-240V, 50-60Hz
Lamp Type 195W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		225W Bright mode / 187W Eco mode (< 0.5W Standby)
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		· · · · · · · · · · · · · · · · · · ·
On Screen Display 26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	Security	Security bar, Kensington lock, password protection
Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	On Screen Display	26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian,
Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes	. ,	Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi,
Optional Accessories DLP® Link™ 3D glasses, wireless, ceiling mount Optional Wireless Yes		Vietnamese, Romanian, Indonesian
Optional Wireless Yes	Standard Accessories	
	Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount
RoHS Compliant	Optional Wireless	Yes
	RoHS	Compliant



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

 2 Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

13/03/2017 12:33